

# TÖMLŐBILINCS - 12 mm



**Csavarház:**

Nikkelezett acél

**Csavar:**

Krómmentes galvanizált acél

**Szalag:**

Rozsdamentes acél, AISI 430 EN 1.4016

**Szalag szélesség:**

12 mm



Cikkszám	Atmérő		Csomagolási egység	Meghúzási nyomaték
	legkisebb	legnagyobb		
	mm	mm	db/cs	Nm
TB_015-025_12_W1	15	25	50	8
TB_019-028_12_W1	19	28	50	8
TB_020-032_12_W1	20	32	50	8
TB_025-040_12_W1	25	40	50	8
TB_025-045_12_W1	25	45	50	8
TB_032-050_12_W1	32	50	50	8
TB_040-060_12_W1	40	60	50	8
TB_050-070_12_W1	50	70	50	8
TB_058-075_12_W1	58	75	50	8
TB_060-080_12_W1	60	80	50	8
TB_070-090_12_W1	70	90	50	8
TB_080-100_12_W1	80	100	50	8
TB_090-110_12_W1	90	110	50	8
TB_100-120_12_W1	100	120	50	8
TB_110-130_12_W1	110	130	50	8
TB_120-140_12_W1	120	140	25	8
TB_130-150_12_W1	130	150	25	8
TB_140-160_12_W1	140	160	25	8
TB_135-165_12_W1	135	165	25	8
TB_160-180_12_W1	160	180	25	8
TB_175-205_12_W1	175	205	25	8
TB_200-220_12_W1	200	220	25	8
TB_205-232_12_W1	205	232	25	8
TB_220-240_12_W1	220	240	25	8
TB_240-260_12_W1	240	260	25	8
TB_250-280_12_W1	250	280	25	8
TB_280-300_12_W1	280	300	25	8
TB_300-320_12_W1	300	320	25	8
TB_310-340_12_W1	310	340	25	8
TB_330-360_12_W1	330	360	25	8
TB_350-380_12_W1	350	380	25	8
TB_370-400_12_W1	370	400	25	8